

250 bar



Mod. 5100

Mod. 5100

Pompa per grasso a barile da 16 kg completa di tubo flessibile 1/4" R1T lungh. 1,4 mt, rubinetto e tubetto rigido con testina a 4 griffe.

Hand operated grease pump pail 16 kg with flexible hose 1/4" R1T 1.4 mt length, cock rigid dispenser-pipe and 4 jaw coupler.



Vista componenti
Component view

Mod.	Pressione massima Max. pressure	Portata a colpo Stroke Flow rate	Attacchi Connections	Peso Weight
5100	250 bar	8 gr	M 1/4" BSP	5.5 kg

Dimensioni Sizes (X-Z-Y) (mm)
240x490x630



250 bar



Mod. 5105

Mod. 5105

Pompa per grasso a barile da 16 kg con ruote completa di tubo flessibile 1/4" R1T lungh. 1,4 mt, rubinetto, tubetto rigido con testina a 4 griffe.

Hand operated grease pump pail 16 kg with 2 wheels, flexible hose 1/4" R1T 1.4 mt length, cock, rigid dispenser-pipe and 4 jaw coupler.



Mod.	Pressione massima Max. pressure	Portata a colpo Stroke Flow rate	Attacchi Connections	Peso Weight
5105	250 bar	8 gr	M 1/4" BSP	6 kg

Dimensioni Sizes (X-Z-Y) (mm)
250x510x820



250 bar



Mod. 5115

Mod. 5115

Pompa per grasso a barile da 16 kg completa di tubo flessibile 1/4" R1T lungh. 1,4 mt, rubinetto e tubetto rigido con testina a 4 griffe. Montata su carrello a 2 ruote mod. 4350 con staffa di fissaggio.

Hand operated grease pump pail 16 kg with flexible hose 1/4" R1T 1.4 mt length, cock rigid dispenser-pipe and 4 jaw coupler. Installed on 2 wheels trolley mod. 4350.

Mod.	Pressione massima Max. pressure	Portata a colpo Stroke Flow rate	Attacchi Connections	Peso Weight
5115	250 bar	8 gr	M 1/4" BSP	8 kg

Dimensioni Sizes (X-Z-Y) (mm)
510x580x880

