

Serie snodata - Adjustable arms series

Mod. 9083

Avvolgitubo a molla in acciaio verniciato **serie snodata**, adatto per impieghi a distanze di max. 35 mt.

L'arrotolatore viene fornito di serie senza tubo e può essere utilizzato per il riavvolgimento di tubi per olio, antigelo, grasso, gasolio, aria e acqua a bassa ed alta pressione.

Per la scelta delle tubazioni vedere la tabella a fine pagina.

*Spring driven hose-reels **adjustable arms series**, designed for applications requiring lenght hoses max. 35 mt.*


Reels are standard supplied without hose and it's compatible with oil, antifreeze, grease, diesel, air and water at low and high pressure.

For the hose selection see the table at end of page.



Mod. 9083

Mod. 9777
Staffa Girevole per 9083
Swivel Bracket for 9083



Mod. 9777

Mod. 9530

Avvolgitubo a molla in acciaio inox AISI 304 **serie snodata**, adatto per impieghi a distanze di max. 35 mt.

L'arrotolatore viene fornito di serie senza tubo e può essere utilizzato per il riavvolgimento di tubi per olio, antigelo, grasso, gasolio, aria e acqua a bassa ed alta pressione. Per la scelta delle tubazioni vedere la tabella a fine pagina.

*Spring driven hose-reels made of AISI 304 stainless steel **adjustable arms series**, designed for applications requiring lenght hoses max. 35 mt.*

Reels are standard supplied without hose and it's compatible with oil, antifreeze, grease, diesel, air and water at low and high pressure. For the hose selection see the table at end of page.



Mod. 9530

Mod. 9770
Staffa Girevole per 9530
Swivel Bracket for 9530



Mod. 9770

Mod.	Pressione max. Max. Pressure	Raccordi Connections In - Out	Foro Utile giunto Bore of swivel joint	Ø max Tubo Max. Hose Ø	Max. Lungh.tubo Max. Hose length	Peso Weight	Largh. Fascia Spool width	Mod. staffa girevole su richiesta Swivel bracket on request mod.
9083	200 bar	M 1/2" - F 1/2"	12 mm	1/2"	35 Mt.	26 Kg.	150 mm	9777
9530	200 bar	M 1/2" - F 1/2"	12 mm	1/2"	35 Mt.	26 Kg.	150 mm	9770

Dimensioni Sizes (X-Z-Y) (mm)
260x590x600
260x590x600



Tubazioni suggerite per questi modelli di arrotolatori, in base ai tipi di fluido ed alla distanza di impiego.

Advised selection of flexible hoses for the above reels, according to the type of fluid and the work lenght.

Tipo di Fluido Kind of fluid	Ø tubo Hose Ø	20 mt.	25 mt.	30 mt.	35 mt.
Oilio / Antigelo Oil / Antifreeze	1/2" R1T 140 bar	28720	28725	28730	28735
Grasso Grease	1/4" R2T 400 bar	4520	4525	4530	4535
Acqua alta pressione High pressure water	3/8" R2T 400 bar	4720	4725	4730	4735
Aria Compressa / Acqua Compressed air/ Water	3/8" - 20 bar	3820	3825	3830	3835